

**Product Code:** REKIP4KD4W

**Description:** 4 Channel Full HD 1TB NVR & 4 x Dome Camera CCTV Kit



### 4 Channel HD 1TB NVR

<b>System</b>	
Operating System	LINUX
Recording Bandwidth	50Mbps
POE	4CH (<100 Metres per. Channel)
<b>Video &amp; Audio</b>	
Video Input	4CH
Audio Output	1CH
<b>Display</b>	
Output	1 x HDMI, 1 x VGA
Display Split	1/4
Resolutions	1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 2560*1440, 3840*2160
<b>Recording</b>	
Compression	H.264 / H.265 Selectable
Resolution	2 Megapixel
Record Rate (Main Stream)	2 Megapixel
Recording Mode	Manual/Motion Detection/Schedule
<b>Playback &amp; Backup</b>	
Sync Playback	2 Megapixel
Backup Mode	Network/2 x USB2.0
<b>Network</b>	
Ethernet	RJ-45 port (100/1000Mbps)
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP
Network Monitoring	Web browser, Client Software, Android & IOS
<b>Storage</b>	
Internal HDD	1TB HDD
<b>General</b>	
NVR Power Consumption	<7W (Without Hard Disk)
NVR Power Source	IEEE802.3af
Operation Condition	0°C to +55°C / 10% – 90%
Dimensions	300mm x 227mm x 53mm
<b>Power</b>	
Operating Voltage	12V DC

### 3.6mm Lens 2MP IP Dome Camera - White

Sensor Size	1/2.7"
Lens	3.6mm Fixed
Viewing Angle	88°
Effective Pixels	2MP (1920 x 1080)
Ingress Protection	IP66
Minimum Illumination	0.05 Lux
Auto Electronic Shutter	1/5 ~ 1/20000s
IR Distance	30 Metres
Compression	H.265
Video bit rate	256Kbps ~ 8Mbps
Interface	RJ45 10M / 100M Ethernet
Network Functions	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Network Monitoring	Web browser, Client Software, Android & IOS
Power	12V DC/POE
Consumption	≤ 7W
Dimensions	Ø100mm x 82 mm
Weight	260g
Storage Temperature	-30°C to +60°C
Operating Temperature	-30°C to +55°C

2 x 18.3 Metre Twisted 2-Pair CAT-5e Cables, Internal Grade, Black  
System Power Supply & Power Lead  
Software CD  
Manual  
HDMI Lead  
Mouse Control  
Remote Control (Batteries Included)

### Accessories

IPCDBW IPC Deep Base - White

