

rekor HD Technical Specification

ESP
ScolmoreGROUP

Product Code: RHD4KB2G

Description: 4 Channel HD 500GB DVR & Grey Bullet Camera CCTV Kit



4 Channel HD 500GB DVR

System	
Operating System	Linux
Video & Audio	
Video Input	4 Channel BNC
Audio Input	4 RCA Inputs
Audio Output	1 Channel RCA
Construction	
Material	Steel - Body ABS - Faceplate
Display	
Video Output	1 x HDMI, 1 x VGA & 1 x BNC
Display Split	Single / Quad
Resolution	1024 x 768, 1280x720, 1280x1024, 1440x900, 1920x1080, 1080 x 1440, 3840 x 2160
Recording	
Video/Audio Compression	H.265
Resolution	1080P @15fps
Record Rate (Main Stream)	4ch 1080P recording
Recording Mode	Manual/Motion Detection/Schedule
Playback & Backup	
Sync Playback	4ch 1080P playback
Backup Mode	USB2.0 devices
Networking	
Network Connection	Ethernet (RJ45 10M/100M)
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP
Network Monitoring	CMS Windows & Mac, Android & iPhone apps
Storage	
Internal HDD	1 SATA 500GB HDD
Auxiliary Interface	
USB	2 (1 Front & 1 Back)
General	
Power Consumption	<10W (without hard disk)
Operation Condition	0°C – +55°C / 10% – 90%
Dimensions	300mm x 227mm x 53mm
Power	
Operating Voltage	12V DC
Features	
Line Cross Detection	
Perimeter Intrusion Detection	

3.6mm Lens 2MP HD Bullet Camera - Grey

Sensor Size	1/2.8"
Lens	3.6mm Fixed
Effective Pixels	NTSC/ PAL:1920(H) x 1080(V)
Resolution	1080p @25 fps
Ingress Protection	IP66
Minimum Illumination	0.05 Lux
IR Distance	30 Metres
Scanning System	Progressive
Shutter Speed	Automatic
Video Output	1Vpp, 75 ohms
Minimum Object Distance	0.6m
On Screen Display (OSD)	English
Day & Night	Ext / Colour / B&W
Backlight Compensation	Off / User BLC
Wide Dynamic Range	D-WDR (Off/On)
Digital Noise Reduction	2D DNR
Gain Control	Auto
White Balance	ATW
Remote Control Interface	ACP (AHD Coax Protocol)
Power	12vDC
Max Consumption	3.5W
Dimensions	Ø71mm x 151mm
Material	Metal Alloy
Weight	350g
Operating Temperature	-30°C to +50°C

4 Channel DVR
2 x Grey Cameras
2 x 18.3m Shotgun Cables
User Guides
Mounting Screws & Wall plugs

Compatible Products

RHDC36FBW	White 3.6mm Lens Full HD Camera
APPOWMW	Aperta Multiway power supply
APSEPMW	Aperta Multiway BUS Separator
APMONW, APMONB, APMONWG, APMONBG, APAUDH, APAUDHBLK	Compatible Aperta Monitors
ENTERD	Flush Electric Lock
ENTERD-YLR	Surface Electric Lock

Additional Information

Simple 2-core Installation
High-Resolution Colour Camera
Can be customised to customers requirements
Can call address range up to 32 consecutive

