DET-RS - Radio slimline shock sensor







The DET-RS is a compact wireless shock and movement detector that uses configurable sensing technology.

Using an accelerometer, it is capable of detecting vibration or movement of the surface it is fixed to.

The DET-RS has been designed to work with any Scantronic 868MHz narrow-band receiver. Consistent with the DET-RDC the product is available in white, brown and Anthracite grey. Its slimline housing helps it to blend in to a variety of environments, making it ideal for almost any door or window installation.

The products are certified to EN 50131-2-8 and are therefore suitable for use in systems installed to conform to PD 6662:2017 at Grade 2 and environmental class II.

At a glance...

- Grade 2 radio product using Scantronic 868MHz
- 2 years battery life using a CR2 battery
- Sleek and compact design, available in white, brown or Anthracite grey
- Certified to EN50131-2-8:2016
- Accelerometer shock or movement sensing technology



Scantronic product datasheet

DET-RS-W DET-RS-B DET-RS-G

Product specification

Feature	Description	
Part no.	DET-RS-W (white), DET-RS-B (brown), DET-RS-G (grey)	
Power supply	3V CR2 Li/MnO2 battery	
Temperature range	-10 to +55 °C	
Tamper	Front and rear	
Dimensions	103 x 19 x 24mm (H x W x D)	
Weight	40 gms (with battery fitted)	
Compliance	EN50131-2-8 Grade 2 EN61000-6-3:2001 Environmental class II	

Compatible products

Description
40 zone hybrid control panel
30 zone radio control panel
20 zone integrated control panel
40 zone integrated control panel
Radio 10 zone expander
Radio 30 zone expander
Radio receiver
Radio receiver
Radio expander

EatonElectrical Sector EMEA
Route de la Longeraie 7
1110 Morges, Switzerland

EatonSecurity House,
Vantage Point Business Village,
Mitcheldean, Gloucestershire
GL17 0SX

© 2019 Eaton All Rights Reserved July 2019





All other trademarks are property of their respective owners.

