

Technical Specification

Product Code: SC2823PRO4

Description: Astro Bluetooth 2 Module 2 Channel, 7 day Timer, 100 Operations





General Information

Dimensions 90mm x 36mm x 63mm

Display LCD Display
Wire Gauge 0.5 - 2.5mm²
Time Base Quartz Crystal

Quartz Crystal Accuracy (at $\leq \pm 0.5$ Seconds/Day

20°C)

Warranty 3 Years

Power

Battery Type Replaceable CR2032

IEC Protection Class Class II when installed according to

regulations

Construction

Material Self-Extinguishing Thermoplastic
Fixing Surface Mounting or DIN
Distribution Board 35mm DIN-rail (DIN EN 60715)

Mounting
Module Size 2

Outputs

Contact Type 2 x SPDT

Total Switch Rating 16A @ 1.0pf, 230VAC
Min Switching power 1000 mW (10V/10mA)

Maximum Current Rating 10A @ 0.6pf (Inductive)

Outputs

Halogen, Filament Lamp 3000W Fluorescent Lamp 2600W

(Uncompensated)

Fluorescent Lamp (Series 2600W

compensated)

Fluorescent Lamp (Parallel 1300W

Compensated)

Compact Fluorescent Lamp 600W

LED 230VAC 600W

Programming

Programming Schedule 24 Hour, and 7 Day Programmable

Astro Zones User Defined Available Operations 100 Operations

Switching Modes ON, OFF, Pulse, Extra, Permanent

Summer/Winter Time Yes; Automatic

Change

Pulse length - Pulse 00:01 up to 59.59 mm:ss

function (switching time)

Pulse length - Timer (man. 0:00:01 up to 9:59:59 h:mm:ss

switching)

Environment

Ingress Protection IP20 (DIN EN 60529)

Operating Temperature -30°C to 55°C

Accessories

143602 Module Enclosure

RHDC36FBG Grey 3.6mm Lens Full HD Camera
RHDC36FDW White 3.6mm Lens Full HD Camera
RHDC36FDG Grey 3.6mm Lens Full HD Camera

Features

Daily and Weekly programming Astro (sunrise, sunset) program Switching capacity 16A per channel Zero-crossing, LED up to 600W Programmable via App (iOS and Android)

10 years battery reserve

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E:** info@espuk.com | **W:** espuk.com

