## Starcard



## **Application Notes**

The Starcard provides a simple and cost-effective solution in the installation of RS485/422 telemetry systems. The Starcard takes RS485/422 data from one source and distributes it across 8 isolated outputs. The outputs can be wired in a star format or a daisy format to allow up to 31 cameras to be controlled from each output.

8 RS422/485 outputs to allow star wiring of telemetry systems, Tx1500 Keypads and alarm cards. Can also be used when star wiring is required for other systems.

## Features

- Two RJ45 sockets and a screw terminal connector for RS485/422 input from a controller and output to additional daisy chained Starcards
- Eight screw terminal connectors used to output RS485/422 data. Each output can be connected to a single dome / receiver or up to 31 domes / receivers or a combination wired as a daisy chain.
- Can be used with either 2-wire, half duplex; 4-wire, full duplex or simplex systems
- Can also be used with simplex RS485/422 links, for example the RS485 output of multiplexers.
- DB9F connector provides a diagnostic output. This can be used with a laptop PC to monitor the data being sent out of the Starcard via RS232



Building Block Video Ltd

17 Apex Park, Diplocks Way, Hailsham, East Sussex, BN27 3JU, UK Tel: +44 (0) 1323 842727 Support: +44 (0) 1323 444600 Fax: +44 (0) 1323 842728 www.bbvcctv.com

## **Technical Specification**

Power supply	• 12 Vdc 1000mA	
Inputs	<ul><li> 2-wire RS485/422 Simplex</li><li> 4-wire RS422 Full Duplex</li></ul>	
Outputs	<ul> <li>8 x 2 or 4-wire RS485 (switch selectable – default 4-wire).</li> <li>Maximum cable runs approx. 1200mtrs. When the domes / receivers are wired as a daisy chain, the last unit must be terminated and the intermediate units must be unterminated. With a single dome connected to each output, the BBV RS485/422 must be terminated</li> </ul>	
Other outputs	RS232 monitor output via chassis mounted DB9 connector	
Features	LED as power indicator	
Installation	<ul> <li>Supplied in 1U 19in rack mountable metalwork or wall-mounted via the fixing brackets supplied</li> </ul>	
Dimensions	Width 427mm Depth 73mm Height 45mm	
Weight	• 2.2Kg	
Colour	Metal case powder coated RAL7035	



Building Block Video Ltd

17 Apex Park, Diplocks Way, Hailsham, East Sussex, BN27 3JU, UK Tel: +44 (0) 1323 842727 Support: +44 (0) 1323 444600 Fax: +44 (0) 1323 842728 www.bbvcctv.com