



## 3072S

# DIGITAL DIRECTORY MODULE, VANDALCOM SERIES

Module made using double 2.5 mm 316 stainless steel plate, complete with 4 backlit buttons and 32-digit alphanumeric display. Stores up to 1000 user names. Scroll through names using 2 search buttons. Once the name is displayed, simply press the call button. Dimensions: 106x106x56 mm. Compatible only with the art. 4680, 4680C, 4681, 4682HC, 1621, 1621VC, 1622, 1622VC, 1682 and 1682HVC combined with the fronts art. 3262S/x and 3268S/x.

The technical specifications are subject to variations without warning.



### 3072S

# DIGITAL DIRECTORY MODULE, VANDALCOM SERIES

MAIN FEATURES	
Backlighting colour:	Green led
Vandal Resistant rating (IK code):	YES
Product height (mm):	106
Product width (mm):	106
Product depth (mm):	56
Operating temperature (°C):	-25 ÷ 55
Maximum current absorption (mA):	100
SOFTWARE/FIRMWARE SPECIFICATIONS	
No. of storable users:	1000
HARDWARE SPECIFICATIONS	
Total buttons:	4
GENERAL DATA	
Type of finish:	Steel
Product colour:	Steel
COMPATIBILITY	
Simplebus Top audio/video system:	Yes
Building Kit audio/video system:	Yes
Simplebus 2 audio system:	Yes
Simplebus 1 audio system:	Yes
Vip system:	Yes
MOUNTING/INSTALLATION	
Flush-mounted:	Yes
Wall-mounted:	Yes
AUDIO/VIDEO FEATURES	
Display resolution HxV (mm):	
Type of display:	Alphanumeric
CONNECTIVITY	
Type of connections/ports:	RS232, RS485, Infrared
Infrared port:	Yes

The technical specifications are subject to variations without warning.



# 3072S

# DIGITAL DIRECTORY MODULE, VANDALCOM SERIES

CONNECTIVITY		
RS232 ports:	1	
RS485 ports:	1	