



3451S

STAINLESS STEEL SBC DIGITAL 316 SENSE A/V ENT.PAN.



**3451S****STAINLESS STEEL SBC DIGITAL 316 SENSE A/V ENT.PAN.**

Flush-mounted entrance panel (fitted level with the wall) and 3 mm thick stainless steel plate. Certified as IK08. Complete with 128x64 dot LCD graphic display and 15 buttons integrated into the plate, with no mechanical movement. Also functions as an electronic key code. Two search buttons are used to scroll through the names; alternatively, the first letter of the required name can be entered. Once the desired username is displayed, simply press the call button. The call can also be made by directly entering the user code. It can also be used to customise an initial welcome message and can operate with a dual user interface language. Fitted with rfid reader for local door lock control and an additional relay for various uses. It can be used in conjunction with Simplekey electronic keys for automatic updating of names in the directory. It saves up to 4000 user names, 4000 lock-release passwords and 4000 rfid keys. Users and settings are simple to program using PC software art. 1249B (included, with USB connection cable) via a USB or RS485 port, locally on the digital module itself or, thanks to the integrated web server, remotely via connection to the ethernet port. It is compatible with all SBTOP products and functions. Complete with SBC a/v unit Art. 4680C for audio/video/door lock management, and flush-mounted box with concealed fixing screws. To be powered at 33 Vdc using art. 1595. Dimensions 342x182x3 mm

AWARDSDESIGN
MILANO**Merlon**
Awards



3451S

STAINLESS STEEL SBC DIGITAL 316 SENSE A/V ENT.PAN.

MAIN FEATURES

Flush-mounted:	Yes
Wall-mounted:	Yes
Type of sensor:	1/4" CMOS
Horizontal resolution (TVL):	
Signal/noise ratio (dB):	48
Video output:	Composite, 1Vpp, 75 Ohm, PAL
Maximum current absorption (mA):	400
Loudspeaker volume control:	Yes
Operating temperature (°F):	-13 ÷ 131
Vandal Resistant rating (IK code):	

FUNCTIONS

Key button function:	Yes
----------------------	-----

HARDWARE SPECIFICATIONS

Visual signalling:	Yes
Acoustic signalling:	Yes
Sensitive Touch technology:	Yes

GENERAL DATA

Product height (inch):	13.46
Product width (inch):	7.17
Product depth (inch):	0.12

COMPATIBILITY


Simplebus Top audio/video system:	Yes
Simplebus 1 audio system:	Yes



3451S

STAINLESS STEEL SBC DIGITAL 316 SENSE A/V ENT.PAN.

ACCESSORIES



3458

ACCESS CONTROL ACCESSORY MODULE FOR EXTERNAL UNITS, 316

Flush-mounted 3 mm thick stainless steel plate for housing the access control module. Can be used in conjunction with all entrance panels in the 316 range. Dimensions 88x182x3 mm



3460/2

FLUSH-MOUNTED BOX FOR 1- AND 2-BUTTON ENT.PANELS. 316 SERIES

Flush-mounted box for 1- and 2-button ent. panels from 316 Analog series. Dimensions: 164x227.5x56 mm



3460/4

FLUSH-MOUNTED BOX FOR 3- AND 4-BUTTON ENT.PANELS. 316 SERIES

Flush-mounted box for 3- and 4-button ent. panels from 316 Analog series. Dimensions: 164x273.5x56 mm



3460/6

FLUSH-MT.BOX FOR TOUCH-SENSE & 5-6 BUTT.ENT.PAN. 316 SERIES

Flush-mounted box for 5- and 6-button ent. panels from 316 Analog series and for 316 Touch and 316 Sense series ent. panels. Dimensions: 164x323x56 mm



3460/9

FLUSH-MOUNTED BOX FOR 7-8-9-BUTTON ENT. PANELS. 316 SERIES

Flush-mounted box for 7-, 8- and 9-button ent. panels from 316 Analog series. Dimensions: 164x388.5x56 mm



3460/12

FLUSH-MOUNTED BOX FOR 10-11-12-BUTTON ENT.PANELS. 316 SERIES

Flush-mounted box for 10-, 11- and 12-button ent. panels from 316 Analog series. Dimensions: 164x457.5x56 mm



3451S

STAINLESS STEEL SBC DIGITAL 316 SENSE A/V ENT.PAN.

ACCESSORIES



3462/2

WALL-MOUNTED HOUSING SERIES 316 1 & 2 BUT. PANEL

Stainless steel accessory for wall-mounted 316 series entrance panels with 1 or 2 buttons. Dimensions 180x245x57 mm



3462/4

WALL-MOUNTED HOUSING SERIES 316 3 & 4 BUT. PANEL


Stainless steel accessory for wall-mounted 316 series entrance panels with 3 or 4 buttons. Dimensions 180x290x57 mm



3462/6

WALL HOUSING FOR TOUCH-SENSE & 5-6 BUTT.ENT.PAN. 316 SERIES

Stainless steel accessory for wall-mounted entrance panels Art. 3451, 3451/A, 3452, 3453, 3454. Dimensions 180x340x57 mm



1220

NAME TAG SHEETS FOR 316 ANALOG ENTRANCE PANEL

The kit contains 10 sheets of adhesive labels for nameplates and 7 sheets for information modules.



1235A

NAMEPLATE LABEL PRINTING SOFTWARE

Dedicated software for the creation and printing of nameplate and information labels for Ikall, Vandalcom, Quadra and 316 Analog entrance panels. Requires use of adhesive labels art.1217, 1218, 1219 or art.1220. This software is available to download free of charge from the Comelit website



1596B

POWER SUPPLY 33VDC 60W 100-240VAC, PSE CERTIFIED

Power supply unit with 110-230 VAC primary and 33 VDC / 1.8A continuous output for 316 range entrance panels. Equipped with internal protection against current overload and short circuits. Dimensions: 4.17"x3.5"x2.44" (6 DIN modules). PSE certified.



3451S

STAINLESS STEEL SBC DIGITAL 316 SENSE A/V ENT.PAN.

ACCESSORIES



3459

RAINSHIELD WITH LEDS FOR 316 SENSE ST. STEEL ENT. PANEL

Rain shield for 316 series panels.



1595

33VDC POWER SUPPLY UNIT FOR IKALL ENTRANCE PANEL.

Power supply unit with 110-230V primary and 33Vdc 500 mA continuous output, and 1.2A inrush current for external unit with IKALL entrance panel. Equipped with internal protection against overcurrent and short circuits.

Dimensions: 28.2"x3.5"x2.4". (4 DIN modules)