

1/6 OVERVIEW



8241MI



Single-family audio kit with Ikall external unit and Mini intercom, traditional wiring. The kit consists of No. 1 art. 1610 - Ikall series traditional system audio module, No. 1 art. 2702W - Mini series intercom with 2 buttons, No. 1 art. 3316/2 - 2-module stainless steel wall housing, No. 1 art. 33401 - 1-button module, Ikall series, black, No. 1 art. 3311/2S - Ikall series 2-module frame silver, No. 1 art. 3348B - Ikall series electronic key module, No. 1 art. 1538 - traditional series intercom power supply unit.

AWARDS







8241MI

SINGLE-FAMILY AUDIO KIT IKALL AND MINI. 5-WIRE

KIT PRODUC

1610

TRADITIONAL SYSTEM AUDIO SPEAKER UNIT FOR IKALL ENTRANCE PA.



Audio speaker unit for Traditional system, complete with terminal block and double amplificator, watertight loudspeaker and electrets microphone, loudspeaker volume can be adjusted from the front. For use in modules Art. 33400, 33401 and 33402. Dim.: 102x55x38 mm.

MAIN FEATURES - 1610	
Audio system:	Yes
Audio/video system:	Yes
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°C):	-25 ÷ 55



2702W

2-BUTTON MINI DOOR-ENTRY PHONE, TRADITIONAL

MINI series door-entry phone for traditional system with electronic call and key button. Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light. Dimensions: 105x191x28 mm

MAIN FEATURES - 2702W	
Audio system:	Yes
Audio/video system:	No
Flush-mounted:	No
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	No
Induction loop function:	No
Product colour:	White
Sensitive Touch technology:	No
Total buttons:	2



8241MI

SINGLE-FAMILY AUDIO KIT IKALL AND MINI. 5-WIRE

KIT PRODUCT

3348B

ELECTRONIC KEY MODULE, IKALL SERIES



Digital electronic key module with LED keypad backlighting. Blue, white and off lighting options. When a number with between 1 and 8 digits is entered on the keypad, two relays (10A) are activated, allowing the operation of electric door locks or other devices. Dimensions 112x89.5x40 mm.

MAIN FEATURES - 3348B	
Product height (mm):	180
Product width (mm):	112
Product depth (mm):	43
Operating temperature (°C):	-25 ÷ 55
RH max operating humidity (%):	25 ÷ 75
Supply voltage:	12VDC/12VAC (stand-alone) / Simplebus

COORD ATTER TO THE TENT OF THE

1538

4+1 INPUT TRADITIONAL SYSTEM INTERCOM POWER SUPPLY 230VAC

Power supply for audio door entry systems with electronic call generator. 230V AC power supply. 12V AC / 10V DC outputs. Protection against short-circuits and overloads. Dimensions: 105x95x65 mm (6 DIN modules).

MAIN FEATURES - 1538	
Applicable to DIN rail:	Yes
Number of DIN modules:	6



3316/2

POWERCOM 2 MODULE STAINLESS STEEL SURFACE-MOUNTED HOUSING

Stainless steel surface-mounted housing. No. Modules 2, Dimensions 123x213x32,5 mm

MAIN FEATURES - 3316/2	
Product height (mm):	213
Product width (mm):	123
Product depth (mm):	32.5



8241MI

SINGLE-FAMILY AUDIO KIT IKALL AND MINI. 5-WIRE

MAIN FEATURES - 3316/2

33401

IKALL AUDIO MODULE - 1 BUTTON

Module designed for audio speaker unit, with black screen-printed faceplate. Nameplates with LED lighting (options: blue, white or off). To be fitted with an audio speaker unit depending on the cabling system used. Dimensions 112x89.5x32 mm.

MAIN FEATURES - 33401	
Product height (mm):	89.5
Product width (mm):	112
Product depth (mm):	32



3311/2\$

IKALL SERIES 2-MODULES HOLDER FRAME, SILVER FRAME

2 Module frame Silver colour. Dimensions 125x215x37,5mm

MAIN FEATURES - 3311/2S	
Product height (mm):	215
Product width (mm):	125
Product depth (mm):	15.5



8241MI

SINGLE-FAMILY AUDIO KIT IKALL AND MINI. 5-WIRE

ACCESSORIES

1610

TRADITIONAL SYSTEM AUDIO SPEAKER UNIT FOR IKALL ENTRANCE PA.

Audio speaker unit for Traditional system, complete with terminal block and double amplificator, watertight loudspeaker and electrets microphone, loudspeaker volume can be adjusted from the front. For use in modules Art. 33400, 33401 and 33402. Dim.: 102x55x38 mm.



2702W

2-BUTTON MINI DOOR-ENTRY PHONE, TRADITIONAL

MINI series door-entry phone for traditional system with electronic call and key button. Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light. Dimensions: 105x191x28 mm



1538

4+1 INPUT TRADITIONAL SYSTEM INTERCOM POWER SUPPLY 230VAC

Power supply for audio door entry systems with electronic call generator. 230V AC power supply. 12V AC / 10V DC outputs. Protection against short-circuits and overloads. Dimensions: 105x95x65 mm (6 DIN modules).



3348B

ELECTRONIC KEY MODULE, IKALL SERIES

Digital electronic key module with LED keypad backlighting. Blue, white and off lighting options. When a number with between 1 and 8 digits is entered on the keypad, two relays (10A) are activated, allowing the operation of electric door locks or other devices. Dimensions 112x89.5x40 mm.



3316/2

POWERCOM 2 MODULE STAINLESS STEEL SURFACE-MOUNTED HOUSING

Stainless steel surface-mounted housing. No. Modules 2, Dimensions 123x213x32,5 mm



33401

IKALL AUDIO MODULE - 1 BUTTON

Module designed for audio speaker unit, with black screen-printed faceplate. Nameplates with LED lighting (options: blue, white or off). To be fitted with an audio speaker unit depending on the cabling system used. Dimensions 112x89.5x32 mm.



8241MI

SINGLE-FAMILY AUDIO KIT IKALL AND MINI. 5-WIRE

ACCESSORIES



3311/2S IKALL SERIES 2-MODULES HOLDER FRAME, SILVER FRAME

2 Module frame Silver colour. Dimensions 125x215x37,5mm