

HEADQUARTERS

FAAC spa
Via Calari 10 - 40069 Zola Predosa (BO)
Tel. +39 051 61724 - Fax +39 051 758518
info@faac.it - www.faacgroup.com

FAAC SUBSIDIARIES

FAAC AG
Tel. +41 41 8713440
Fax +41 41 8713484
Altdorf, Switzerland
www.faac.ch

FAAC FRANCE
Tel. +33 4 72218700
Fax +33 4 72218701
Corbas, France
www.faac.fr

FAAC GMBH
Tel. +49 8654 49810
Fax +49 8654 498125
Freilassing, Germany
www.faac.de

FAAC MIDDLE EAST BRANCH
Tel. +971 42146733
Fax +971 42146734
Dubai Airport Free Zone, UAE
www.faac.ae

F.A.A.C. SA
Tel. +34 91 6613112
Fax +34 91 6610050
Madrid, España
www.faac.es

FAAC UK LTD.
Tel. +44 1256 318100
Fax +44 1256 318101
Basingstoke Hampshire, UK
www.faac.co.uk

FAAC AUSTRALIA PTY LTD
Tel. +61 2 87565644
Fax +61 2 87565677
Homebush - Sydney, Australia
www.faac.com.au

FAAC NORD
Tel. +33 1 69191620
Fax +33 1 69191621
Massy, France
www.faac.fr

FAAC INDIA PVT. LTD
Tel. +91 120 3934100/4199
Fax +91 120 4212132
Noida - Delhi, India
www.faacindia.com

FAAC POLSKA SP.ZO.O.
Tel. +48 22 8141125
Fax +48 22 8142024
Warszawa, Polska
www.faac.pl

F.A.A.C. SA Delegación Cataluña
Tel. +34 93 4362000
Fax +34 93 4368225
Barcelona, España
www.faac.es

FAAC BENELUX
Tel. +32 50 320202
Fax +32 50 320242
Brugge, Belgium
www.faacbenelux.com

FAAC GE.S. I.M.B.H.
Tel. +43 662 8533950
Fax +43 662 85339520
Wals - Siezenheim, Austria
www.faac.at

FAAC INTERNATIONAL INC.
Tel. +1 307 6351991
Fax +1 307 6328148
Cheyenne, USA
www.faacusa.com

FAAC SCANDINAVIA AB
Tel. +46 36 376860
Fax +46 36 370780
Bankeryd, Sweden
www.faac.se

FAAC SHANGHAI
Tel. +86 21 68182970
Fax +86 21 68182968
Shanghai, China
www.faac.com.cn

500 - Zucchetti - 09/2009. The descriptions and illustrations contained in the present brochure are not binding. FAAC reserves the right to undertake product technical modifications without prior notice.



XGuard 10H

LASER SCANNERS

Horizontal safety sensors for barriers



FAAC
Simply automatic.

XGuard 10H

Laser scanner for barriers

FAAC



screens pedestrians in the opening area



Unrestricted configuration of the detection field

Performance


- Double function: opening, maintenance of presence and/or safety
- An alternative to cutting loops into the road surface.
- Detects all types of vehicles: electrical vehicles, vehicles made of composite materials, trucks with trailers...
- It is possible to detect the vehicle's trajectory as it is approaching or moving away, reducing false barrier raises
- Screens pedestrians in the opening area, preventing false activations
- Maximum detection field of 9.9m x 9.9m
- It is possible to switch off the LED indicators in order to make the equipment more discreet

Applications:

- Opening, presence and/or safety detection for rising barriers

Ease of installation:

- Alternative to induction loops; installation and adjustment without the need for impact on the roadway
- Unrestricted, easy configuration of the opening and presence detection areas
- Positioning of the detection fields facilitated by means of 3 visible infrared points
- Option of mounting the device to the left or right of the barrier
- Automatic learning of the environment
- Xguards require a universal remote for programming (order as separate engineers tool)
- Mounting bracket is available separately



9.9m x 9.9m @ 2% remission factor

Technical Specifications

Technology	LASER scanner, time of flight measurement
Detection mode	motion and presence
Max Detection range	9.9m x 9.9m
Emission characteristics IR LASER Red visible LASER	Wavelength 905 nm; max. output pulse power 75W Wavelength 650 nm; max output CW power 3mW
Supply voltage	10-35V DC@sensor side
Power consumption	< 5W
Cable length	5m (standard), max 10m
Response time Motion detection Presence detection	Typ 200ms (adjustable) Typ 20ms; max 80ms
Output	2 electronic relays (galvanic isolation - polarity free)
Input	1 optocoupler (galvanic isolated - polarity free)
LED signals	1 blue LED; power on status 1 orange LED; error status 2 bi-coloured LED's: detection/output status (green: no detection; red: detection)
Dimensions	125mm (L) x 93mm (D) x 70mm (H) (mounting bracket +14mm)
Material	PC/ASA
Colour	Black
Rotation angles on bracket	-5° to +5° (lockable)
Tilt angles on bracket	-3° to +3°
Protection degree	IP65
Temperature range	-30°C to +60°C if powered; -10°C to +60°C unpowered
Humidity	0-95% non-condensing
Vibrations	<2G
Pollution on front screens	max 30%; homogenous
Norm conformity	2006/95/EC: LVD; 2002/95/EC: RoHS 2; 2004/108/EC: EMC; EN60529:2001; IEC 60825-1:2007 Laser class 1 & 3R; EN 609550-1:2005; EN61000-6-2:2005EMC; EN61000-6-3:2006 EMC